

MATERIA 6



MATERIA 6 is a new decorative product.

This product is appreciated both on the Italian and the International market because of its high decorative power, prestige, quality, application easiness and environmental respect.

MATERIA 6 is therefore a new product that allows you to create new decorations and enrich your homes with elegance and harmony.

MATERIA 6 is produced with an accurate selection of the raw materials.

The application cycle includes the colored MATERIA BASE whit InTone Color System and the application, over the same, of the MATERIA 6 applied by brush (when the colored coat is completely dried).

PREPARATION OF THE MATERIA BASE FOR THE DECORATION

The product MATERIA 6, very easy to apply, needs our MATERIA BASE colored with InTone Color System to obtain decorations comparable to those attained by the experts in the art.

Choose the desired color among the InTone Color System available nuances. Accurately mix the toners in Materia Base™ using a putty knife or a spoon.

It is possible to apply the MATERIA BASE colored coat by a paint roller, or by spray with a proper external air mixture compressor.

It is also recommended to apply two coats of the product; the first one by adding 15-20% of water, the second one by the addition of 20-25% of water.

PREPARATION OF THE PRODUCT AND THE MATERIA 6 DECORATION

MATERIA 6 is an ecological decoration with a medium-level of transpiration, based on pigments and resin of a very high quality in an aqueous solution.

Apply the product on the wall by painting on the MATERIA BASE colored coat previously applied with the procedures above mentioned. MATERIA BASE colored coat must be completely dried.

The decoration can be performed by using a small brush, with alternate and crossed tracts, by perfectly applying the paint to avoid possible lumps. Decorate the wall without discontinuances and restarts, and avoid, if possible, to apply a second coat where already painted.

PRODUCT CHARACTERISTICS

Yield	100-150 ml/m ²
Drying time:	Set to touch: 2-3 hours Complete polymerization: 20-25 days
Tools cleaning:	Wash with warm water.
Wall cleaning:	After at least a month from the application, the wall can be cleaned with warm water using a sponge.
pH:	6.5 – 8.5
Specific weight:	1– 1.10
Viscosity:	6000-8000 cps at 25°C
Storage and processing temperature:	minimum + 7°/5°C Maximum +35°/40°C



06/04/20

TECHNICAL DATA SHEET

MATERIA 6



Appearance of the product:	silver
Flammability:	This product is completely free of flammable solvents, being totally in aqueous phase.
Dilution:	ready made
VOC regulation:	Water-based L subclass.
V.O.C. maximum limit allowed:	200 g/l
V.O.C. content in the ready made product:	<50 g/l

Shake and mix before use.

During the application of the MATERIA BASE colored coat and MATERIA 6 follow the normal industrial hygiene practices.

Keep the product out of the reach of children.



A.C.M. Sas di Danese R. & C. | Via XXV Aprile, 62 | 20010 Bareggio /MI

PHONE +39 02 903 611 48 | laboratorio@acm-italy.com | www.acm-italy.com | www.materia-italy.com 2