TECHNICAL DATA SHEET

MATERIA 7



Materia 7 is completely formulated using water-based chemicals It is environmentally friendly product, made up of selected raw materials such as aqueous emulsion resin polymer, thickening agents, defoamers, preservatives, etc.

Materia 7 is a decorative product that keeps with modern trends, favoring natural, warm and enveloping colours, blended together for a decorative effect that is slightly velvety to the touch, elegant and refined, yet not too flashy.

SURFACE PREPARATION

The wall that is to be decorated must be clean, so remove any impurities and sand it down, if need be. If required, apply a coat of duly diluted acrylic primer for indoors. Apply the decorative product cyclically, which entails, in the first instance, applying two white or coloured coats of base coat, applying two coats (make sure the first coat is completely dry before proceeding with the second). When the second base coat is completely dry, apply two coats of Materia 7 decorative product, using a brush.

APPLYING THE BASE COAT

The white or coloured base coat is applied using a brush, a wool roller, or a spray gun with a suitable compressor. We recommend applying two coats, the first with 20-25% water dilution and the second with 15-20% water dilution.

APPLYING MATERIA 7

Before proceeding with the decoration, make sure the base coat that was previously applied to the wall is dry. Apply two coats of Materia 7 decorative product using a brush, making sure the first coat is completely dry before applying the second.

Then start applying the first coat of Materia 7 using a brush; cross the brush strokes to optimize the distribution of the decorative product on the wall. The second coat, once the first is completely dry, will follow the same application method, taking care to proceed without interruptions and restarts, thus avoiding unattractive overlaps.

Keep this product out of reach of children.

PRODUCT CHARACTERISTICS

APPROX. COVERAGE: two coats of 5-7 m² per 1lt. of product

DRYING: 2-3 hours to the touch. Complete polymerization 20 - 25 days

PH: 6.5 - 9

SPECIFIC WEIGHT: 1 - 1.2

VISCOSITY: 7500 - 10000 cp at 25°C DILUTION: Product is ready for use

STORAGE AND PROCESSING TEMPERATURE: minimum 7°C, maximum 35°C sensitive to frost

VOC regulation: subcategory L water-based. Maximum VOC limit allowed 200gr/lt. Ready to use product VOC

content lower than 50 g/l. APPLICATION TOOLS: Brush

CLEANING THE WALL: with a sponge at least one month after applying Materia 7

TECHNICAL DATA SHEET

MATERIA 7



TOOL CLEANING: Wash with warm water