08/04/20

TECHNICAL DATA SHEET

MATERIA 3



MATERIA 3 is a new decoration, completely water based, appreciated for its high decorative power, prestige and quality.

APPLICATION CYCLE

The application cycle includes the MATERIA BASE (not colored), applied with a natural bristle brushes or shorthair rollers or by spray with a suitable compressor plus spray gun.

We advise the application of two coats, the first one diluted at 20-25%, the second one at 15-20%.

Application of the decoration:

Before proceeding with the decoration, ensure that the MATERIA BASE, previously applied to the wall, is completely dry.

Then, proceeding with the application of colored Materia 3.

Using a brush, apply the decorative paint with crosshatched strokes, making sure that the paint is distributed evenly over the wall surface. To avoid brushing over previously painted areas, it is advisable to complete the whole surface in one go, without interruptions.

The application of the MATERIA 3 makes the surface slightly rough.

We recommend conducting a small test before starting work.

PRODUCT CHARACTERISTIC

Packaging:	10 liters can
Coverage:	125 – 175 ml/m²
Drying time:	to the touch 2-3 ore – Total polymerization 20-25 days
Tools cleaning:	Wash with warm water
ph:	6,5 – 8,5
Specific weight:	0,9 - 1,1
Viscosity:	6000 – 8000 cp a 25° C
Minimum storage and working temperature:	+ 7° C
Maximum storage and working temperature:	+ 35° C
Product aspect:	silver aspect
Inflammability:	Product completely free of flammable solvents, totally
	free in the aqueous phase
Dilution:	Ready to use

Shake and stir before use.

During the application of MATERIA BASE and MATERIA 3 following the normal health and safety regulations. Keep the product out of the reach of children.

V.O.C. Regulation:

Subcategory L, water-based. VOC limit value 200 g/L VOC content of the ready to use product: < 50 g/l.